VX1945wm

19" WIDESCREEN VIEWDOCK™ LCD

WITH IPOD® DOCK IN MULTIMEDIA BASE

Digital media comes to life with the ViewDock™

Stop, Dock and Rock – the ViewSonic 19" VX1945wm ViewDock™ LCD is the ultimate entertainment display. **Dock your iPod®** to access all your digital content. **Boost** your handheld photos and videos and view on the large widescreen display. Hear your digital content with built-in stereo speakers and additional **subwoofer** for unparalleled audio performance – or go silent with the **headphone jack**. Manage your digital media with the integrated **8-in-1 digital card reader** for camera cards. Connect your digital devices through the **4 USB ports**. Chat on-line using the built-in **microphone**. The super-fast 5ms response time screen lets you watch movies or play games free from blurs or ghosting. Your desktop experience will never be the same once you bring it all together with the VX1945wm ViewDock and iPod®[1].

IT'S NOT JUST THE ULTIMATE ENTERTAINMENT DISPLAY - IT'S A VIEWSONIC.

MAKE YOUR DESKTOP A DIGITAL MEDIA DESTINATION

> **Multimedia base with iPod® dock**
Multimedia base features iPod® dock, 8-in-1 card reader, microphone, headphone jack, 4 USB ports and subwoofer.

> **Widescreen performance for movies and games**
Play games and watch movies on the 19" viewable widescreen with 1440 x 900 resolution.

> **Enhanced audio performance**
Built-in stereo speakers and additional integrated subwoofer.

> **ClearMotiv™ 5ms video response time**
Super-fast 5ms video response time delivers images free from blurs or ghosting.

> **Ultra-high brightness and contrast**
See the Difference with ViewSonic's award-winning screen performance. 700:1 contrast levels and 300cd/m² brightness deliver rich, crisp, detailed images.

> **Stylish slim-bezel design with glossy piano-black finish**
Gloss piano-black / matt black finish and ultra-modern design for the latest in styling.

> **OptiSync® digital/analogue inputs expand your connectivity**
Multi-mode input technology supports both digital and analogue signals for ultimate compatibility and configuration flexibility.

> **PC and Mac® compatible**

MORE THAN 2000 AWARDS
VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
the choice of professionals

VX1945wm

19" WIDESCREEN VIEWDOCK™ LCD WITH IPOD® DOCK IN MULTIMEDIA BASE

ViewSonic
the choice of professionals

LCD	Type	19" Wide TN colour TFT active matrix WXGA+ LCD
	Display Area	41.0cm horizontal x 25.6cm vertical, 48.3cm diagonal
	Pixel Pitch	0.285mm
	Optimum Resolution	1440 x 900@60Hz
	Pixel Clock	140MHz
	Contrast Ratio	700:1 (typ.)
	Viewing Angle	160° horizontal, 160° vertical (at 10:1), 160° horizontal, 160° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Light Source	Long life, 40000 hrs. (typ.)
	Brightness	300cd/m^2
	Panel Surface	Anti-glare
VIDEO INPUT	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Digital	DVI-D (TMDS, 100 ohm)
	Frequency	F_h: 30~82kHz, F_v: 50~85Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
COMPATIBILITY	PC	VGA up to 1440 x 900 non-interlaced
	Mac®[2]	Power Mac™ G3/G4/G5 up to 1440 x 900 non-interlaced
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	ViewDock™	iPod® dock (Made for iPod® certified)
	Audio	1 x 3.5mm stereo audio line-in, 1 x 3.5mm stereo audio line-out
	Headphone	3.5mm mini stereo jack
	Card Reader	8-in-1 digital card reader
	USB	USB 2.0 hub, 1x upstream (4-pin Typ B)/4x downstream (4-pin Typ A)
	Power	3-pin AC plug (CEE22) (Display), DC plug (base)
AUDIO	Speakers	2 x 2 watt integrated stereo speakers
	Subwoofer	1 x 3 watt intergrated into base
	Microphone	Integrated into base
POWER	Voltage	AC 100– 240V, 50/60Hz (auto switch), internal power supply (Display)
	Consumption	59 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	Power, menu [1], up, down, select [2], mute, subwoofer volume up/down
	OSD[3]	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), ViewMatch® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITONS	Temperature	0°C–40°C
	Humidity	20%–80% (non-condensation)
DIMENSIONS	(W x H x D mm)	450 x 449 x 212 (with stand) 450 x 341 x 66 (without stand) 545 x 520 x 260 (packaging)
WEIGHT	Net	5.7kg (with stand) 4.7kg (without stand) 7.7kg
REGULATIONS		CE, CB, NEMKO/ERGO[4], ISO13406-2 (pixel failure class II), GOST-R + 20 original copies hygienic, UL, cUL, FCC-B, ENERGY STAR®, NOM, MPR II, SASO, BSMI, CCC, PSB, C-TICK, WEEE, RoHS
POWER MANAGEMENT		Meets MPR II and ENERGY STAR® standards
SECURITY		Kensington® security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, DVI cable, audio cable, USB cable, iPod® adapter, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

RoHS COMPLIANT™

ISO 9001 FM 40187 ISO 14001 EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom
Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux Tel: +32 (0)56 85 26 27
ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 (0)9 5406 4070
ViewSonic Italy Tel: +39 02 73 95 50 22
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands Tel: +31 (0)20 491 9254
ViewSonic Norway Tel: +47 (0) 22 88 17 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

[1]iPod® must be purchased separately. [2] May require optional Mac adapter. [3] Some features may not available on all inputs. [4] Equivalent to TÜV/ERGO.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VX1945wm 10/06-UK